



# Alarm.com PoE Video Door Station Data Sheet

ADC-VDB755P

[www.alarm.com](http://www.alarm.com)

© 2024 Alarm.com. All rights reserved. 240930

## Key Features

- Power over Ethernet
- Expansive 150° horizontal and 150° vertical field of view ensures customers get a full picture of what's happening at their front door
- Video Analytics with rapid People Detection for faster, more relevant alerts and fewer false notifications
- Full HD resolution, High Dynamic Range (HDR), and infrared night vision
- Two-way audio
- Compatible with the Alarm.com Smart Chime (W115C)
- 2MP live video and saved clip viewing via the app and customer website
- No power module required for compatibility with mechanical or digital chimes
- Compatible with Alarm.com SVRs for continuous recording



## Overview

Introducing the latest addition to Alarm.com's family of entryway solutions — the ADC-VDB755P. The ADC-VDB755P is Alarm.com's first door station and includes Power over Ethernet (PoE) capabilities, for reliable network connection and power supply. This device offers crystal clear 2MP picture and an expansive 150° horizontal and 150° vertical field of view so customers can see and do more at the front door. Alarm.com's powerful People Detection and crisp two-way audio help reduce false notifications while bringing increased awareness and allowing users to communicate with visitors. With support for SVR Recording your customers can locally record encrypted video and view footage from anywhere. Plus - a wide range of operating temperatures increase install flexibility making this a great choice in any environment.

# Specifications

**Recording compression:**  
H.264

**Live resolution options:**  
1440 x 1440

**Recording resolution options:**  
1440 x 1440

**HFoV:**  
150°

**VFoV:**  
150°

**Wi-Fi:**  
N/A

**Ingress protection:**  
IP66

**Low light sensitivity:**  
0 lux with IR

**IR Range:**  
Up to 15 feet (5 meters)

**Image adjustments:**  
Flip, brightness, contrast, saturation, sharpness, exposure

**Operating temperature:**  
-58°F - 122°F (-50°C - 50°C)

**Operating humidity:**  
< 95% (non-condensing) RH

**Dimensions (W x L x D):**  
2.45 x 4.50 x 1.54in  
62.3 x 114.2 x 39.1mm

**Activity Detection:**  
Advanced Video Analytics for People Detection

**Audio:**  
Two-way audio (Full Duplex)

**Compliance:**  
FCC, IC, RCM, CE Class B, UL, RoHS, WEEE, Compliant with Section 889 of the NDAA\*

\*Accurate as of 8/12/24. Visit Alarm.com > Legal > NDAA Statement for the most current information.

# Requirements

**Power:**  
PoE 802.3af

**Ethernet Connection:**  
10/100Mbps RJ-45

# Status light guide

**Off:**  
Power off

**Blinking yellow:**  
Camera power cycling

**Solid red:**  
No local or Internet connection

**Blinking red:**  
Power on, camera booting

**Alternating red and green:**  
Camera resetting to factory default

**Solid green:**  
Connected to Alarm.com

# Included accessories

- ADC-VDB755P Video Door Station
- Wall anchors (x2) & screws (x2)
- Foam gasket